METEOR


N-TYPE TOPCON TECHNOLOGY

TIER 1 BloombergNEF

Deutsche Qualität Garantiert

710W- 730W

CME-132BDS



23.53%
MAXIMUM EFFICIENCY

132
HALF CELLS

- N-type cell technology
- High efficiency and power output
- Cost-effective scalability and market dominance
- Low degradation and high durability
- No LID or LeTID


Ver..25.10.1

30 YEARS
Performance Warranty

up to **15** YEARS*
Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.

OUR PERFORMANCE WARRANTY




AESOLAR
Since 2003


LID RESISTANT
PID RESISTANT
SALT CORROSION RESISTANT
SAND RESISTANT
AMMONIA RESISTANT
HIGHLY STABLE AND TOUGH


AE CME-132BDS 710W-730W

N-TYPE TOPCON TECHNOLOGY PV MODULE

BIFACIAL • DOUBLE-GLASS







Electrical specifications (STC*):

Nominal max. power	Pmax (Wp)	710	715	720	725	730
Maximum operating voltage	VMPP (V)	40.90	41.10	41.30	41.50	41.70
Maximum operating current	IMPP (A)	17.36	17.40	17.43	17.47	17.51
Open-circuit voltage	Voc (V)	48.70	48.90	49.10	49.30	49.50
Short-circuit current	Isc (A)	18.37	18.40	18.43	18.46	18.49
Module efficiency	η (%)	22.88	23.04	23.21	23.37	23.53
Power tolerance	(W)			0~+5		
Maximum system voltage	(V)			1500		
Maximum series fuse rating	(A)			30		

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance Pmax: ±3%

Electrical specifications (NMOT*):

Nominal max. power	Pmax (Wp)	550	555	560	565	570
Maximum operating voltage	VMPP (V)	39.11	39.39	39.66	39.93	40.20
Maximum operating current	IMPP (A)	14.06	14.09	14.12	14.15	14.18
Open-circuit voltage	Voc (V)	46.20	46.55	46.89	47.23	47.57
Short-circuit current	Isc (A)	14.88	14.90	14.93	14.95	14.98

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

Bifacial electrical specifications


Max.power front-side Pmax f ront (Wp)	710		715		720		725		730	
Backside Power Gain	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Total equivalent power $P_{max\ equ}$ (Wp)	746	781	751	787	756	792	761	798	767	803
Module efficiency η (%)	24.03	25.17	24.20	25.35	24.37	25.53	24.54	25.70	24.70	25.88

*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

Mechanical and design specification

Cell type	n-Type TOPCon technology, half-cut cells
No. of cells	132
Bifaciality	80 ± 5%
Front cover	2.0 mm glass, high transmission, AR coated, tempered
Encapsulation	POE
Back cover	2.0 mm white glazed glass, tempered
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable (Including Connector)	1 x 4 mm², 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2383 mm x 1302 mm x 30 mm
Weight	37 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m²
Snow load	5400 Pa or 550 kg/m²
Fire rating	Class A (according to UL 790)

Packaging information



Temperature ratings

Operating temperature Temp.	-40 to +85°C
coefficient ofPmax	-0.29 %/°C
Temp. coefficient ofVoc	-0.24 %/°C
Temp. coefficient ofIsc	0.040 %/°C
Nom. operating cell temp. NOCT	43 ± 2°C

SYSTEM AND PRODUCT CERTIFICATIONS

IEC 61215 IEC 61730
Regular Production Surveillance

www.tuv.com

IEC 62716 (Ammonia corrosion)
IEC 61701 (Salt mist corrosion)
IEC 60068 (Sand and dust)
IEC 62804 (PID resistance)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.

AESOLAR Since 2003

+49 8231 978268 0
sales@ae-solar.com
www.ae-solar.com

AESOLAR
Senefelderstraße 23
86368 Gersthofen, Germany